



AILEEN

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Education and Culture Executive Agency (EACEA). Neither the European Union nor EACEA can be held responsible for them. PROJECT REFERENCE NO. 101103507



Co-funded by
the European Union

Health and Safety requirements – safe operation

Iván García Arrizabalaga
CESOL



CenSec
CENTER FOR DEFENCE, SPACE & SECURITY



PRI
PERFORMANCE REVIEW INSTITUTE

ODÜ KATAMER

Fraunhofer
FIT

TURKISH
AEROSPACE

Mercantec

IPH

mtc
where progress happens

SICNOVA

Laser
AKADEMIE

ASTURIAS HUB
DEFENSA

CESOL

ISO

IDONIAL
TECHNOLOGY CENTRE



FAN 3D

Brunel
University
London

Agenda Items



- Overview of Fuel Gases and Oxidants in Brazing
- General Hazards and Preventive Measures for Fuel Gases
- Hoses and Non-Return Valves: Hazards, Risks, and Safety Measures
- Ventilation and Fume Hazards in Brazing
- Personal Protective Equipment and Air Quality Monitoring
- Project and Consortium Information



AILEEN

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Education and Culture Executive Agency (EACEA). Neither the European Union nor EACEA can be held responsible for them. PROJECT REFERENCE NO. 101103507



Co-funded by
the European Union

Overview of Fuel Gases and Oxidants in Brazing



CenSec
CENTER FOR DEFENCE, SPACE & SECURITY



PRI
PERFORMANCE REVIEW INSTITUTE

ODÜ KATAMER

Fraunhofer
FIT

TURKISH
AEROSPACE

Mercantec

IPH

mtc
where progress happens

SICNOVA

Laser
AKADEMIE

ASTURIAS HUB
DEFENSA

CESOL

ISO

IDONIAL
TECHNOLOGY CENTRE



FAN 3D

Brunel
University
London

Risks of fuel and oxidant mixtures in brazing operations



Explosion and Fire Hazards

Fuel and oxidant mixtures can ignite spontaneously causing fires and explosions in brazing operations.

Causes of Ignition

Ignition can occur due to heat, sparks, or open flames interacting with combustible gas mixtures.

Safety Protocols

Proper storage, handling, leak detection, ventilation, and flashback arrestors are essential to prevent accidents.

Commonly used fuel gases and their specific hazards

Fuel Gas Usage in Brazing

Fuel gases combined with oxygen or compressed air generate the heat necessary for brazing processes.

Acetylene Properties


Acetylene is highly flammable and forms explosive mixtures with air and oxygen, requiring careful storage and handling.

Safety Risks of Acetylene

Risks include flashbacks, backfires, and violent decomposition if stored above 1.5 bar without stabilizers.

Leakage Hazards

Leaks can cause rapid ignition and explosions, emphasizing the need for proper safety devices and leak detection.



Hazards of propane, butane, natural gas, hydrogen, and other gases



Propane and Butane Risks

Propane and butane are heavy, flammable gases that accumulate in low areas, increasing explosion risks in confined spaces.

Natural Gas Hazards

Methane is flammable and explosive when mixed with air between 5% and 15%, with leaks often invisible and dangerous.

Hydrogen Danger

Hydrogen burns with an almost invisible flame and diffuses rapidly, making leak detection and explosion prevention challenging.

Other Gas Precautions

Gases like ethylene and acetylene require precise mixing with oxygen for safe flame characteristics in brazing applications.



AILEEN

General Hazards and Preventive Measures for Fuel Gases

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Education and Culture Executive Agency (EACEA). Neither the European Union nor EACEA can be held responsible for them. PROJECT REFERENCE NO. 101103507



Co-funded by
the European Union



CenSec
CENTER FOR DEFENCE, SPACE & SECURITY



PRI
PERFORMANCE REVIEW INSTITUTE

ODÜ KATAMER

Fraunhofer
FIT

TURKISH
AEROSPACE

Mercantec

IPH

mtc
where progress happens

SICNOVA

Laser
AKADEMIE

ASTURIAS HUB
DEFENSA

CESOL

ISO

IDONIAL
TECHNOLOGY CENTRE



FAN 3D

Brunel
University
London

General hazards and risks associated with fuel gases



Explosive Gas Mixtures

Fuel gases combined with oxygen or air can create highly explosive conditions, especially if backflow occurs.

Flashback Hazards

Flames traveling back into equipment can ignite gases internally, risking catastrophic equipment failure.

Pressure Setting Risks

Incorrect pressure settings can destabilize flames and increase gas leak risks, escalating workplace hazards.

Preventive measures for safe operation

Installation of Safety Devices


Installing flashback arrestors, non-return valves, and pressure relief devices is vital for operational safety.

Compliance with ISO Standards

Adhering to ISO 5175 standards ensures proper safety protocols are followed during installation and operation.

Leak Detection and Ventilation

Continuous leak detection and proper ventilation are essential for preventing hazardous operational conditions.





AILEEN

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Education and Culture Executive Agency (EACEA). Neither the European Union nor EACEA can be held responsible for them. PROJECT REFERENCE NO. 101103507



Co-funded by
the European Union



CenSec
CENTER FOR DEFENCE, SPACE & SECURITY



PRI
PERFORMANCE REVIEW INSTITUTE

ODÜ KATAMER

Fraunhofer
FIT

TURKISH
AEROSPACE

Mercantec

IPH

mtc
where progress happens

SICNOVA

Laser
AKADEMIE

ASTURIAS HUB
DEFENSA

CESOL

ISO

IDONIAL
TECHNOLOGY CENTRE



FAN 3D

Brunel
University
London

Hoses and Non-Return Valves: Hazards, Risks, and Safety Measures

Hazards and risks associated with hoses



Leaks and Gas Permeation

Damaged or worn hoses can leak fuel gases or oxygen, creating explosive mixtures in the work area.

Pressure Bursting Risks

Incorrect pressure or degraded hoses risk bursting, causing sudden gas release and fire or explosion hazards.

Dangerous Gas Backflow

Incorrect hose connections can cause gas backflow, producing highly explosive hazardous mixtures inside hoses.

Hazards and risks associated with non-return valves



Preventing Gas Backflow

Non-return valves prevent reverse gas flow, avoiding dangerous mixing of oxygen and fuel gases.

Explosive Gas Mixture Risk

Backflow without valves can create explosive mixtures within hoses and regulators.

Flashback Propagation Danger

Absence of non-return valves increases the risk of flame traveling backward causing system failure.

Safety measures for hoses and non-return valves

INDUSTRIAL HOSES & NON-RETURN VALVES



WEAR SAFETY GEAR



FOLLOW SAFETY PROCEDURES



LEAK DETECTED



EMERGENCY SHUT OFF



Non-Return Valves Usage

Non-return valves prevent reverse gas flow and are mandatory under ISO 5175 standards for welding equipment.

Flashback Arrestors Integration

Combining non-return valves with flashback arrestors stops flames from traveling back into hoses and equipment.

Hose Inspection and Maintenance

Regular inspection for cracks and leaks is essential; damaged hoses must be replaced immediately for safety.

Color Coding and Pressure Control

Proper hose color coding and pressure control prevent cross-connections and reduce backflow risks.



AILEEN

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Education and Culture Executive Agency (EACEA). Neither the European Union nor EACEA can be held responsible for them. PROJECT REFERENCE NO. 101103507



Co-funded by
the European Union

Ventilation and Fume Hazards in Brazing



CenSec
CENTER FOR DEFENCE, SPACE & SECURITY



PRI
PERFORMANCE REVIEW INSTITUTE

ODÜ | **KATAMER**

Fraunhofer
FIT

TURKISH
AEROSPACE

Mercantec

IPH

mtc where progress happens

SICNOVA

Laser
AKADEMIE

ASTURIAS HUB
DEFENSA

CESOL

ISO

IDONIAL
TECHNOLOGY CENTRE



FAN 3D

Brunel
University
London

Hazards and risks from fumes and toxic metals



Toxic Metal Fumes

Heating filler metals like zinc, cadmium, or lead releases harmful fumes causing respiratory irritation and metal fume fever.


Health Risks of Prolonged Exposure

Long-term exposure to toxic metal fumes can lead to serious health issues including kidney damage and cancer.

Flux Vapors Hazards

Fluoride and borate vapors from fluxes can irritate workers' eyes, skin, and lungs during brazing.

Risks from incomplete combustion and poor ventilation




Incomplete Combustion Hazards

Incomplete combustion of fuels produces carbon monoxide, a deadly, colorless and odorless gas.

Effects of Poor Ventilation

Poor ventilation lowers oxygen levels, increasing risk of dizziness, unconsciousness, and death.

Safety measures for ventilation and fume extraction



Adequate Ventilation Importance

Ensuring adequate ventilation removes harmful fumes and maintains safe oxygen levels in work areas.

Fume Extraction Systems

Extraction hoods and portable fume collectors capture hazardous fumes directly at the brazing source.



AILEEN

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Education and Culture Executive Agency (EACEA). Neither the European Union nor EACEA can be held responsible for them. PROJECT REFERENCE NO. 101103507



Co-funded by
the European Union



CenSec
CENTER FOR DEFENCE, SPACE & SECURITY



PRI
PERFORMANCE REVIEW INSTITUTE

ODÜ KATAMER

Fraunhofer
FIT

TURKISH
AEROSPACE

Mercantec

IPH

mtc
where progress happens

SICNOVA

Laser
AKADEMIE

ASTURIAS HUB
DEFENSA

CESOL

ISO

IDONIAL
TECHNOLOGY CENTRE



FAN 3D

Brunel
University
London

Personal Protective Equipment and Air Quality Monitoring

Use of PPE and respirators for fume protection



Importance of PPE

PPE is essential when ventilation cannot fully control hazardous fume exposure in the workplace.

Respirator Use

Respirators approved for metal fumes and chemical vapors provide critical protection against inhalation hazards.

Monitoring air quality and handling fluxes safely



Air Quality Monitoring

Regular air monitoring detects harmful gases like carbon monoxide, ensuring safety in enclosed spaces.

Safe Flux Handling

Proper storage and application of fluxes reduce harmful vapor release and ensure safe usage.

Iván García Arrizabalaga
igarcia@cesol.es



AILEEN

